

Softa-Man acute / Softalind acute / Softalind 999



Safety Data Sheet

according to UK REACH Regulation

Issue date: 31/08/2012

Revision date: 21/03/2023

Supersedes: 13/08/2020

Version: 2.1

SDS No: 00056-0230

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Softa-Man acute / Softalind acute / Softalind 999

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Hand disinfectant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

B. Braun Medical AG
Seesatz 17
CH-6204 Sempach - Switzerland
T +41 (0) 58 / 258 50 00
info.bbmch@bbraun.com

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

Supplier

B. Braun Medical Ltd.
Thornccliffe Park Estate, Brookdale Road
Sheffield S35 2PW, UK - Medical Information Department
T +44 (0)114 225 9000
medinfo.bbmuk@bbraun.com

1.4. Emergency telephone number

Emergency number : INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP Regulation

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 1	H318
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes serious eye damage. May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to GB CLP Regulation

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Propan-1-ol; Butanone

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H318 - Causes serious eye damage.
H336 - May cause drowsiness or dizziness.

Softa-Man acute / Softalind acute / Softalind 999

Safety Data Sheet

according to UK REACH Regulation
SDS No: 00056-0230

- Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe vapours.
P280 - Wear eye protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
P501 - Dispose of contents and container to an approved waste disposal plant.
- Extra phrases : Applies for those countries where this product is classified as medicinal product; as ready for use medicinal product, this product is not subject to labelling obligation according to the CE directives in these countries.

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP) :



- Signal word (CLP) : Danger
- Hazardous ingredients : Propan-1-ol; Butanone
- Hazard statements (CLP) : H318 - Causes serious eye damage.
- Precautionary statements (CLP) : P280 - Wear eye protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
- Extra phrases : Applies for those countries where this product is classified as medicinal product; as ready for use medicinal product, this product is not subject to labelling obligation according to the CE directives in these countries.

2.3. Other hazards

- Other hazards not contributing to the classification : Vapours may form explosive mixture with air.
Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP Regulation
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	< 55	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Propan-1-ol	(CAS-No.) 71-23-8 (EC-No.) 200-746-9 (EC Index-No.) 603-003-00-0 (REACH-no) 01-2119486761-29	< 25	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
Butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	$\geq 1 - < 3$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	(50 ≤C ≤ 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures**4.1. Description of first aid measures**

First-aid measures general	: Data of item 4 do partly not refer to the use and the regular employing of the product (in this sense consult package leaflet and expert information), but to liberation of major amounts in case of accidents and irregularities. Take off immediately all contaminated clothing. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after eye contact	: Wash immediately with plenty water (during 20 minutes), also under eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Do not induce vomiting. Drink plenty of water. Call a physician immediately. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media	: Water spray. Dry powder. Carbon dioxide. Alcohol resistant foam.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Product is not explosive. Explosive vapour/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Precautionary measures fire	: Cool endangered containers with water spray jet.
Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Vapours are heavier than air and may spread along floors. Vapours may form explosive mixture with air. Collect contaminated fire-fighting water, avoid any release into the sewerage. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Safety Data Sheet

according to UK REACH Regulation
SDS No: 00056-0230

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8. Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Keep away from food, drink and animal feeding stuffs.
Incompatible materials : oxidizing materials. alkaline earth metals. alkali metals.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

See Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
WEL STEL (OEL STEL)	5760 mg/m ³ (calculated)

Softa-Man acute / Softalind acute / Softalind 999



Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

Ethanol (64-17-5)	
WEL STEL (OEL STEL) [ppm]	3000 ppm (calculated)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Propan-1-ol (71-23-8)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-1-ol
WEL TWA (OEL TWA) [1]	500 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	625 mg/m ³
WEL STEL (OEL STEL) [ppm]	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Monitoring methods	
Monitoring methods	A specific exposure sampling method is not available
Biological monitoring methods	A specific exposure sampling method is not available

Ethanol (64-17-5)	
DNEL/DMEL (General population)	
Acute - local effects, inhalation	1900 mg/m ³
Long-term - systemic effects, oral	343 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	950 mg/m ³
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.96 mg/l
PNEC aqua (marine water)	0.79 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.6 mg/kg dwt
PNEC sediment (marine water)	2.9 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.63 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	580 mg/l

Propan-1-ol (71-23-8)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1723 mg/m ³
Long-term - systemic effects, dermal	136 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	268 mg/m ³

Softa-Man acute / Softalind acute / Softalind 999



Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1036 mg/m ³
Long-term - systemic effects, oral	61 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	80 mg/m ³
Long-term - systemic effects, dermal	81 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	22.8 mg/kg dwt
PNEC sediment (marine water)	2.28 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.2 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	96 mg/l

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Data of item 8 do partly not refer to the use and the regular employing of the product (in this sense consult package leaflet and expert information), but to liberation of major amounts in case of accidents and irregularities.

Hand protection:

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	6 (> 480 minutes)	0,7		EN ISO 374

Eye protection:

Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection:

Long sleeved protective clothing (DIN EN ISO 6530)

Respiratory protection:

No personal breathing protective equipment is normally required

Device	Filter type	Condition	Standard
Breathing apparatus with filter	Type A - High-boiling (>65 °C) organic compounds	In the event of insufficient ventilation:	EN 14387

Safety Data Sheet

according to UK REACH Regulation
SDS No: 00056-0230

Environmental exposure controls:

Avoid release to the environment.

Other information:

Data of item 8 do partly not refer to the use and the regular employing of the product (in this sense consult package leaflet and expert information), but to liberation of major amounts in case of accidents and irregularities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless.
Odour	: alcoholic.
Odour threshold	: No data available
pH	: 2.7 – 3.2
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -114 °C Ethanol
Freezing point	: No data available
Boiling point	: 78 °C Ethanol
Flash point	: 21 °C DIN 51755
Auto-ignition temperature	: 425 °C Ethanol
Decomposition temperature	: > 700 °C Ethanol
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 59 hPa Ethanol
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 0.855 – 0.865 g/cm ³ at 20 °C
Solubility	: Water: Miscible
Log Pow	: -0.3 Ethanol
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Not oxidising.
Lower explosive limit (LEL)	: 3.5 vol % Ethanol
Upper explosive limit (UEL)	: 15 vol % Ethanol

9.2. Other information

VOC content	: < 80 %
Solvent content	: < 80 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour. No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with: oxidizing materials. alkali metals. alkaline earth metals.

10.4. Conditions to avoid

Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

alkali metals. alkaline earth metals. Oxidizing agent.

Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

10.6. Hazardous decomposition productsNo hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO₂).**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
 Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
 Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)

LD50 oral rat	10470 mg/kg
LD50 oral	6200 mg/kg
LD50 dermal rabbit	15800 mg/kg
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat (Vapours)	30 mg/l/4h

Propan-1-ol (71-23-8)

LD50 oral rat	> 8000 mg/kg
LD50 dermal rabbit	4032 mg/kg
LC50 Inhalation - Rat (Vapours)	> 33.8 mg/l/4h (OECD 403 method)

Butanone (78-93-3)

LD50 oral rat	3300 mg/kg (OECD 401 method)
LD50 dermal rabbit	58000 mg/kg (Bibliographic results)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
 pH: 2.7 – 3.2

Serious eye damage/irritation : Causes serious eye damage.
 pH: 2.7 – 3.2

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, nausea, dizziness. Irritation of mucous membranes. If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

SECTION 12: Ecological information**12.1. Toxicity**

Ecology - general : No ecotoxicological data about this product are known.

Softa-Man acute / Softalind acute / Softalind 999



Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LC50 fish 1	11200 mg/l 96 h
EC50 Daphnia 1	5012 mg/l 48 h, Daphnia magna
ErC50 algae	275 mg/l

Propan-1-ol (71-23-8)	
LC50 fish 1	4555 mg/l Pimephales promelas
EC50 Daphnia 1	3644 mg/l Daphnia magna (Water flea)
NOEC chronic crustacea	> 100 Daphnia magna (Water flea)
NOEC chronic algae	1150 mg/l Chlorella sp.

Butanone (78-93-3)	
LC50 fish 1	3220 mg/l 96 h, Pimephales promelas
EC50 Daphnia 1	5091 mg/l 48 h, Daphnia magna (Water flea)
ErC50 algae	1150 mg/l 16 h, Pseudomonas

12.2. Persistence and degradability

Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Softa-Man acute / Softalind acute / Softalind 999	
Log Pow	-0.3 Ethanol

Ethanol (64-17-5)	
Bioconcentration factor (BCF REACH)	0.06
Log Pow	-0.3

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Ecological injuries are not known or expected under normal use. When low concentrations are discharged correctly into adapted biological sewage treatment plants, interference with the degradation activity of activated sludge is not likely. Do not flush into surface water or sewer system

Safety Data Sheet

according to UK REACH Regulation
SDS No: 00056-0230

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 07 06 04* - other organic solvents, washing liquids and mother liquors

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1987	UN 1987	UN 1987	UN 1987	UN 1987
14.2. UN proper shipping name				
ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	Alcohols, n.o.s. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)
Transport document description				
UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II, (D/E)	UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II	UN 1987 Alcohols, n.o.s. (Ethanol ; Propan-1-ol), 3, II	UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II	UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640C
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 33

Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0230

Orange plates	:	33 1987
Tunnel restriction code (ADR)	:	D/E
EAC code	:	•3YE
Transport by sea		
Special provisions (IMDG)	:	274
Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T7
Tank special provisions (IMDG)	:	TP1, TP8, TP28
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-D
Stowage category (IMDG)	:	B
MFAG-No	:	127
Air transport		
PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
Special provisions (IATA)	:	A3, A180
ERG code (IATA)	:	3L
Inland waterway transport		
Classification code (ADN)	:	F1
Special provisions (ADN)	:	274, 601, 640C
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	1
Rail transport		
Classification code (RID)	:	F1
Special provisions (RID)	:	274, 601, 640C
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001
Transport category (RID)	:	2
Hazard identification number (RID)	:	33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU-Regulations**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Safety Data Sheet

according to UK REACH Regulation
SDS No: 00056-0230

VOC content : < 80 %

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

All chapters have been modified since the previous version.

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to GB CLP Regulation

Flam. Liq. 2	H225	On basis of test data
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.